International Test Facilities

Snowmass 2021 Community Planning Meeting Session 175: Accelerator research centers and test facilities for future accelerators

Virtual

6 October 2020

Ralph W. Aßmann, DESY





Introduction

Scope of this talk

From Tor Raubenheimer:

One of the key goals of the Snowmass'21 Accelerator Frontier is to address the question "What are the time and cost scales of the R&D and associated test facilities as well as the time and cost scale of the facility?"

- There are a large number of accelerator test facilities and R&D efforts in the other regions, mainly in Europe and Asia.
- Problem: No chance to even list all acronyms and explain them in the 10 minutes of this talk.
- Please take this talk as a short glimpse at some of the international test facilities that exist, are discussed or being implemented...
- Focus here on technologies with strong R&D needs to prove basic feasibility for a collider: test and
 demonstration facilities are of key importance for advancing towards a linear collider! Several collider studies
 (ILC, FCC, ERL-based, ...) and associated test facilities perform outstanding R&D, but are more advanced
 and not covered here for time reasons. Also: Focus on LOI submissions to the Snowmass'21 process.
 - Muon collider test facility (input from Nadia Pastrone, Daniel Schulte, Mark Palmer).
 - Plasma / dielectric accelerator test facilities

Muon Collider R&D

(material and input from Nadia Pastrone, Daniel Schulte, Mark Palmer)

- The recent update of the European strategy has pointed out muon colliders as subject of interest and R&D for the future of particle physics.
- This will likely result in the future proposal and implementation of an international test or demonstrator facility for muon collider R&D, too early to be defined now in detail.
- A working group has been formed to scientifically justify the investment into a demonstration programme before the next strategy process and to define what this programme should contain.
- The core test facility might be a cooling facility. There will certainly be prototype development and most likely beam tests.
- Full tests for both the proton and the positron-based sources for a muon collider might be excluded due to limited resources.
- Beam tests will be relevant since for example the LEMMA design currently uses collision beta-functions of 0.2 mm in both planes, which I only saw in the plasma collider proposals.


Muon Colliders: MAP Scenario

Input:

 π , μ produced from Proton Bunch ~10 14 , 1 m long ~0 —1 GeV/c, $\epsilon_{\rm t,N}$ ~ 0.02 m

Output:

Cooled μ^+ and μ^- bunch ~10¹² / bunch $\epsilon_{t,N}$ ~ 0.00002 m,



Target

Produce pions

Capture

Collect and cool muons from pion decay

Cooling

Single pass →
Ring coolers,
Improve final
cooling
PIC cooling ??


Collider rings


for

0.125, 1.5, 3, 6 TeV designed



Muon Collider (Proton-driven)





First demonstration in MICE (UK)
But need new facility with RF and
stages and significantly more cooling



DESY. International

Plasma / Dielectric Accelerator Test Facilities

International landscape of test facilities highly populated

High gradient, ultra-compact new acceleration technologies often **originate in universities or smaller groups**. Technology and setup is comparably inexpensive and easily accessible.

- There exist more than 30 experiments, setups and facilities in Europe and Asia, mainly for plasma acceleration but also a handful for dielectric accelerators.
- The field is only recently moving to the large accelerator labs in Europe and Asia. Smaller facilities live on and continue producing outstanding accelerator science and innovative solutions.

Here: Focus on efforts with international scope and ambition. Also: Focus on topics and facilities with **LOI submissions** to the Snowmass'21 process.

- Apologies to efforts in Japan (Osaka RIKEN, SPring-8) who are building up an important Japanese facility on the site of RIKEN-SPring-8.
- Apologies to highly successful facility in Korea and impressive facility plans in China.
- Apologies to the many local or national facilities in Europe not mentioned.

As said before: just a short glimpse to international facilities...

ALEGRO

Towards an Advanced Linear International Collider

- See LOI by Brigitte Cros and Patric Muggli and AF6 presentation by B. Cros.
- ALEGRO LOI provides a list of test facilities and highlight goals.

ALEGRO LOI for Snowmass2021



Towards an Advanced Linear International Collider

Contacts: Brigitte Cros¹, Patric Muggli²

1 CNRS, Université Paris Saclay, Orsay, France, email: <u>brigitte.cros@universite-paris-saclay.fr</u> 2 Max Planck Institute for Physics, Munich, Germany, email: <u>muggli@mpp.mpg.de</u>







Endorsed by the Advanced and Novel Accelerator panel of ICFA https://icfa.fnal.gov/

Authors: B. Cros¹, E. Gschwendtner (CERN), S. Hooker (JAI, U. Oxford), P. Muggli², J. Osterhoff (DESY), M. Peskin (SLAC), P. Piot (NIU, ANL), J. Power (ANL), C. Schroeder (LBNL), J.-L. Vay (LBNL), J. Viera (IST)

On behalf of ALEGRO collaboration member list at http://www.lpgp.u-psud.fr/icfaana/alegro/alegro-members


B. Cros et al


B. Cros et al			
Facility	Readiness	ANA	Specific Goals Based in EU
BELLA	Operating	LWFA	e ⁻ , 10 GeV, multi-GeV staging
kBELLA	Design study	LWFA	e ⁻ , 1 GeV, kHz rep rate, 1 kW avg. power
KALDERA 🛨	Start 2025	LWFA	e ⁻ , 1 GeV, kHz rep rate, 1 kW avg. power efforts towards high average
EuPRAXIA 🜟	Design study	LWFA, PWFA	e ⁻ , 5 GeV, reliability
AWAKE 🛨	Operating	PWFA p-driven	e ⁻ , beam quality, multi-GeV, HEP fixed target exp.
FACET II	Start 2020	PWFA	e ⁻ , 10 GeV boost, beam quality, e ⁺ acceleration
FLASHForward	Operating	PWFA	e ⁻ , 1.5 GeV, beam quality, high rep rate, 10 kW avg. power
AWA	Operating	SWFA	e ⁻ , sub-GeV, high charge, beam shaping, TBA and CWA

AWAKE

Proton-driven plasma acceleration based at CERN

- See LOI's by AWAKE and AF6 presentation by M. Wing and P. Muggli.
- Test facility can also serve pre-collider goals, e.g. search for dark photons and deep inelastic scattering experiments.







AWAKE LOI



AWAKE opportunity: high energy proton bunches available today as wakefields driver

- **♦ CERN LHC:** 6.5TeV, 1x10¹¹p⁺ ⇔ 104kJ

Drive ~GV/m accelerating fields in a single, km-long plasma

AWAKE applications to HEP (AF6 LOI "high energy physics applications of the AWAKE acceleration scheme"):

- ♦ Search for dark photons (beam dump experiments)
- ♦ Strong field quantum electrodynamics
- ♦ High-energy electron-proton collisions
- ♦ Compact electron injector using the RHIC-EIC proton beam

Rapid progress has been made by the AWAKE experiment at CERN (first experiments Dec. 2016):

- ♦ Controlled self-modulation (SM) long p⁺ bunch
- ♦ Acceleration of externally injected e⁻ to 2GeV
- → Development of plasma sources: laser ionized rubidium vapor (10m), discharge, helicon



P. Muggli

M. Wing

EuPRAXIA

European plasma accelerator with FEL + other applications

- See LOI by EuPRAXIA, AF6 presentation by M. Ferrario.
- Test/demonstration facility can also serve pre-collider goals, e.g. FEL for high beam quality, e+, multi-stage.
- Start of pilot user operation planned for 2028:
 - EU-funded CDR (incl. resource estimates, planning) started in 2015, has been completed and published.
 - Bringing together facilities at 48 members and observers institutes in 15 countries.
 - Aiming at 2 construction sites. Frascati/Italy started.
 - 569 M€ project (full cost) with >100 M€ already approved.
- Project submitted to 2021 ESFRI Roadmap Update at EU (European Strategy Forum for Research Infrastructures). Formal government support: Italy, Czech, Portugal, Hungary, UK





Phase I: 388 M€ comprises the design, full preparation costs, (including laser technology), implementation of all excellence centres and the cost of construction at the site at INFN-INF, Frascati, Italy. Personnel costs of 126 M€ Phase II: 53-181 M€ is the construction cost of the laser-driven EuPRAXIA leg (dependent on site choice) and termination costs. Personnel costs of 29 M€

Average Annual Operation Costs (covered by the local host institutes) : 30 M€ (PWFA 11.6 M€, LWFA 11.3 M€ excellence centres 6.3 M€, RI management 0.8 M€)

- 2) We already have binding commitments for more than 100 M€, mainly through Italy.
- 3) Lead country is Italy which will also host the EuPRAXIA headquarters in the National Laboratory at Frascati. Czech Republic has provided a letter of financial and political support. Portugal, Hungary and UK have provided letters of political support.
- 4) EuPRAXIA has received **20 support letters** from industrial companies plus other from large representative bodies, including TIARA and LEAPS
- 5) Upcoming next will be the ESFRI review. Once we are on the roadmap we will have the preparatory phase for EuPRAXIA, during which we will finalise the preliminary studies and estimates from our CDR and from the ESFRI application.

Dielectric Laser Accelerators

ACHIP International Collaboration

- See LOI by and AF6 presentation by Joel England et al.
- This is an international collaboration, relating to several test facilities in- and outside of the US.
- European facilities involve SwissFEL at PSI (Switzerland), Erlangen and ARES/SINBAD at DESY (Germany).
- Good example of international coordination and synergy.

Gradient and Energy Scalability:

- High-gradient operation with 850 MeV/m average electron gradient and 0.3 MeV energy gain and phase/dispersion control. Higher gradients possible -- 1.8 GV/m axial fields experimentally demonstrated in fused silica DLA. (UCLA, D. Cesar 2018)
- POCs have demonstrated key concepts needed for energy scaling: transverse and longitudinal focusing, optical pre-bunching and injection, net acceleration, integrated waveguide coupling, extended transport, staging of laser pulses.
- ACHIP aims to develop a cm-scale 1 MeV tabletop accelerator by FY21

Dielectric Laser Accelerators

Snowmass AF6 Meeting Sept 23, 2020

R. J. England

Current and Future Test Facilities

SLAC

Current Test Facilities:

UCLA Pegasus: 1-8 MeV photoinjector+linac; Ti:Sapphire laser; low-charge, norm. emittance ~ 30nm-rad High gradient and high energy gain demonstration experiments

Stanford: 30 to 100 keV nanotip emission sources for low-energy structure evaluation

FAU Erlangen: 30 kV SEM and supertip field emission source test stands; 2µm laser testing

Future Planned (Funded) Test Facilities (1 to 5 year timeline):

PSI SwissFEL 3 GeV beam line - dedicated DLA diagnostic and vacuum chamber Laser driven undulator, wakefield studies, radiation damage testing

DESY SINBAD 100 MeV beamline -- short bunches (few fs); optically microbunched beams anticipated Net acceleration experiments; particle deflection/streaking

FAU and Stanford: 1 MeV university test bench: demonstrate basic staging and integrated component capabilities; proposed outcome of ACHIP

Other Potential Test Facilities (1 to 5 year timeline):

NLCTA (SLAC) – currently in minimal operation mode; used in earlier (2013-2015) experiments ATF (BNL) – high power CO₂ laser; capabilities for hosting advanced accelerator experiments

5

Other Test Facilities on Specific Topics (not in short ALEGRO list)

Advancing spin polarization and hybrid plasma accelerators

- e+e- colliders and physics reach enhanced by spin polarized beams
- See LOI and AF6 presentation by M. Büscher and A. Lehrach
- International Partners: Germany, Greece, China, and USA → several facilities involved

Snowmass 2021 – Letter of Interest


Aug/31/2020

Polarized targets for laser-plasma applications

M. Büscher^{1,2}, A. Hützen^{1,2}, J. Böker³, R.W. Engels³, R. Gebel³, A. Lehrach^{3,4}, P. Gibbon⁵, A. Pukhov⁶, R.W. Aßmann⁷, T.P. Rakitzis^{8,9}, L. Ji^{10,11}, T. Schenkel¹², X. Wei¹³

- ¹Peter Grünberg Institut (PGI-6), Forschungszentrum Jülich, 52425 Jülich, Germany
- ² Institut für Laser- und Plasmaphysik, Heinrich-Heine-Universität Düsseldorf, 40225 Düsseldorf, Germany
- ³ Institut für Kernphysik, Forschungszentrum Jülich, 52425 Jülich, Germany
- ⁴ JARA-FAME Forschungszentrum Jülich and RWTH Aachen University, 52056 Aachen, Germany
- ⁵ Institute for Advanced Simulation, Jülich Supercomputing Centre, Forschungszentrum Jülich, 52425 Jülich, Germany
- ⁶ Institut für Theoretische Physik I, Heinrich-Heine-Universität Düsseldorf, 40225 Düsseldorf, Germany
- ⁷ DESY, Notkestraße 85, 22607, Hamburg, Germany
- ⁸ Department of Physics, University of Crete, 71003 Heraklion-Crete, Greece
- 9 Institute of Electronic Structure and Laser, Foundation for Research and Technology-Hellas, 71110 Heraklion-Crete, Greece
- ¹⁰ State Key Laboratory of High Field Laser Physics, Shanghai Institute of Optics and Fine Mechanics, Shanghai 201800, China
- ¹¹ CAS Center for Excellence in Ultra-intense Laser Science, Shanghai 201800, China
- ¹² Accelerator Technology and Applied Physics Division, Lawrence Berkeley National Laboratory, Berkeley, California 94720, USA
- ¹³ Thomas Jefferson National Accelerator Facility, Newport News, VA 23606, USA

- Use a laser-generated electron beam for driving plasma wakefields in a second stage
 → HQ electron beam from ultra-compact setup
- See LOI and AF6 presentation by A. Irman
- Several facilities involved




Thank you for your attention!

Backup slides afterwards



LEMMA source Accumulator ring – R&D

 \triangleright Extraction of e⁺ bunches to one or more muon production target-lines, produced μ [±] are accumulated in two Accumulator Rings (AR), each μ^{\pm} bunch is "built" by several passages through the targets, to be then delivered to the fast acceleration chain



- **1. TARGETS** Several options to be explored for the μ source
- **2.BEAM PHYSICS** \rightarrow design e⁺ and μ [±] rings with very high energy acceptance, design of Interaction Region and Separation Region for 3 beams (e⁺, μ ⁺, μ ⁻)
- **3.HIGH FIELD MAGNETS** \rightarrow need to focus 45 GeV e⁺ and 22.5 GeV μ^{\pm} together in a short low β function IR \rightarrow high gradient, large aperture and compact quadrupoles. Design multi-targets μ^{\pm} production line requires efficient 3-beams separation design, minimising particle losses, with high field, large aperture dipoles
- **4.RF CAVITIES** → high gradient SCRF cavities able to cope with a high average train current (~100 mA)
- **5.MUON COOLING** \rightarrow longer μ^{\pm} lifetime at production allows moderate cooling mechanism to further reduce production emittance.
- 6. MUON RECOMBINATION